UL Solutions | Product iQ®

System Unit BT-200, HFC-227ea engineered extinguishing system units, 25, 42 or 50 bar

File Number: EX29934

COMPANY

Blazetech Systems Ltd
100 Avebury Boulevard
Milton Keynes, MK9 1FH United Kingdom

SYSTEM UNIT INFO

BT-200, HFC-227ea engineered extinguishing system units, 25, 42 or 50 bar
Engineered, Halocarbon

CLEAN AGENT EXTINGUISHING SYSTEM UNITS	VALUE
Extinguishing Agent (ASHRAE Designation)	HFC-227ea

MANUALS AND BULLETINS

Part No.	Description	Date/Rev
BTCAGS-UL-HFC-MNL	Installation and Design Manual	R1 (07/28/2026)

SYSTEM UNIT INFORMATION

Operating Pressure at Temperature	Minimum Operating Temperature	Maximum Operating Temperature
25 bar (360 psig) at 21 °C	-10 C (14 F)	60 C (140 F)
42 bar (610 psig) at 21 °C	-10 C (14 F)	60 C (140 F)
50 bar (725 psig) at 21 °C	-10 C (14 F)	60 C (140 F)

THESE INSTALLATIONS REQUIRE THE USE OF THE LISTEE'S FLOW CALCULATION SOFTWARE:

Software Name/Version
HFC227ea, Version 4.00

Report Date: 2026-05-08
Revision Date: 2026-09-22

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."