

Valves | Indicating Valves (Butterfly or Valve Type) | **Indicating Valves, Butterfly or Ball Type**

Models BT 5402, BT 5403

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
BT 5402	Butterfly Valve, Grooved Ends	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a, b, c, d
BT 5403	Butterfly Valve, Wafer Style	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12	(50, 65, 80, 100, 125, 150, 200, 250, 300)	300	(2065)	a, b, c, d

- Remarks:**
- a. Available with dual supervisory closed switches.
 - b. FM Approved for indoor and outdoor service.
 - c. FM Approved for aboveground installations only.
 - d. Available with one supervisory switch for valve closed position (intended for bypass lines only) and one supervisory switch for valve open position

Details

Category	Indicating Valves, Butterfly or Ball Type
Class of Work	1112 - Indicating Valves
Approval Standard	FM 1112 - Indicating Valves (Butterfly or Ball Type)
Certification Type	FM Approved
Listing Country	United Kingdom

Company

BLAZETECH SYSTEMS LTD
100 AVEBURY BOULEVARD,
MILTON KEYNES, United Kingdom