

Model BT 5221

File Number: EX29987

COMPANY

Blazetech Systems Ltd

100 Avebury Boulevard

Milton Keynes, MK9 1FH United Kingdom

MODEL INFO

BT 5221

Base-Valve Design

BASE VALVE HYDRANTS

Base Valve Size	Number of Hose Outlets	Hose Outlet Size	Number of Pumper Outlets	Pumper Outlet Size	Rated Pressure, psig (kPa)	Monitor Elbow
5-1/4 in. (135 mm)	2	2-1/2 in. (65 mm)	--	--	250 (1723)	3 in., 4 in.
5-1/4 in. (135 mm)	2	2-1/2 in. (65 mm)	1	4 in. Threaded (100 mm Threaded), 4-1/2 in. (115 mm), 5 in. Threaded (125 mm Threaded), 5 in. Nonthreaded (125 mm Storz)	250 (1723)	--
5-1/4 in. (135 mm)	3	2-1/2 in. (65 mm)	1	4 in. Threaded (100 mm Threaded), 4-1/2 in. (115 mm), 5 in. Threaded (125 mm Threaded), 5 in. Nonthreaded (125 mm Storz)	250 (1723)	--
5-1/4 in. (135 mm)	4	2-1/2 in. (65 mm)	--	--	250 (1723)	--
5-1/4 in. (135 mm)	2	2-1/2 in. (65 mm)	2	4 in. Threaded (100 mm Threaded), 4-1/2 in. (115 mm), 5 in. Threaded (125 mm Threaded), 5 in. Nonthreaded (125 mm Storz)	250 (1723)	--

ADDITIONAL DETAILS

Breakaway Traffic Feature Available

Yes

Protective Interior Coating Available

--

Report Date: 2026-07-18

Revision Date: 2026-07-17

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."