



Model BT 5351

File Number: EX29989

COMPANY
Blazetech Systems Ltd
100 Avebury Boulevard
Milton Keynes, MK9 1FH United Kingdom

MODEL INFO
BT 5351
Basket Type

PRODUCT DETAILS			
End-configuration	Size, NPS	Rated Pressure, psi (kPa)	Approximate Loss of Head at 15 ft/sec (4.6 m/sec) flow velocity
Flange by Flange 3 in.		200 (1378)	3.2 psi (23 kPa)
Flange by Flange 4 in.		200 (1378)	3.5 psi (25 kPa)
Flange by Flange 5 in.		200 (1378)	3.6 psi (25 kPa)
Flange by Flange 6 in.		200 (1378)	4.6 psi (32 kPa)
Flange by Flange 8 in.		200 (1378)	4.2 psi (29 kPa)
Flange by Flange 10 in.		200 (1378)	3.8 psi (27 kPa)
Flange by Flange 12 in.		200 (1378)	5 psi (35 kPa)

Report Date: 2026-07-17
Revision Date: 2026-07-17

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."