

Model BT 5933A

File Number: EX29993

COMPANY
Blazetech Systems Ltd
100 Avebury Boulevard
Milton Keynes, MK9 1FH United Kingdom

MODEL INFO
BT 5933A

ATTRIBUTES AND RATINGS

Body Type	Nom Pipe Size, NPS	End Configuration	Relief Set Outlet Relief Pressure Range, psi (kPa)	Relief Type	Relief Model
Angle	3, 4, 5, 6, 8	Class 125 – Flanged by Flanged, Class 150 – Flanged by Flanged, Class 250 – Flanged by Flanged, PN16 – Flanged by Flanged, Grooved by Grooved, Grooved by Flanged, Grooved by Class 125 Flanged, Grooved by Class 150 Flanged, Grooved by Class 250 Flanged, Grooved by	300 (2068)	--	

GENERAL

Installation Limitations

End configurations are intended to be installed on systems not exceeding end configurations' working capabilities.

Report Date: 2026-07-17
Revision Date: 2026-07-17

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."