

Low-expansion Foam Liquid Concentrate

BT FFFP 6%

File Number: EX29980

COMPANY

Blazetech Systems Ltd
100 Avebury Boulevard
Milton Keynes, MK9 1FH United Kingdom

LOW-EXPANSION FOAM LIQUID CONCENTRATE INFO

BT FFFP 6%
Film Forming Fluoroprotein (FFFP)

FOAM CONCENTRATES FOR USE WITH THE FOLLOWING EQUIPMENT

Minimum Storage and Use Temperature

+20 F (-6.7 C)

GENERAL

Hydrocarbon Fuels, percent

6

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Manufacturer and Model	Use Concentration, percent	Size, in.	Orifice Diameter/Setting	Inlet Pressure, psig	Length and Diameter of hose	Discharge Device Manufacturer and Model
ANGUS FIRE LTD, Model UNI225	6	2-1/2	set at 3		100 ft of 2-1/2	ANGUS FIRE LTD, Model F225U nozzle.

NOZZLES

Manufacturer and Model	Size, in.	Inlet Pressure, psig	Fuel
ANGUS FIRE LTD, Model F225U	2-1/2	85	--

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."