

Low-expansion Foam Liquid Concentrate BT Synthetic Fluorine Free Foam 3% (BT-SFFF)

File Number: EX29980

COMPANY

Blazetech Systems Ltd

100 Avebury Boulevard

Milton Keynes, MK9 1FH United Kingdom

LOW-EXPANSION FOAM LIQUID CONCENTRATE INFO

BT Synthetic Fluorine Free Foam 3% (BT-SFFF)

Synthetic Fluorine Free Foam (SFFF)

FOAM CONCENTRATES FOR USE WITH THE FOLLOWING EQUIPMENT

Minimum Storage and Use Temperature

+35 F (1.7 C)

GENERAL

Hydrocarbon Fuels, percent

3

PROPORTIONERS - PORTABLE IN-LINE INDUCTORS

Manufacturer and Model	Use Concentration, percent	Size, in.	Orifice Diameter/Setting	Inlet Pressure, psig	Length and Diameter of hose	Discharge Device Manufacturer and Model
NEWAGE FIRE FIGHTING CO LTD, Model: Newage-ILI-225	3	2-1/2	0.187 inch	112	98 feet and 2-1/2 inch	ANGUS FIRE LTD, Model F225U nozzle

PROPORTIONERS-BLADDER TANKS WITH CONTROLLERS

Manufacturer and Model	Use Concentration, percent	Controller Size, in.	Orifice Diameter, in.	Flow Rate, gpm
FIRE SAFETY DEVICES PVT LTD. and Models FRC-B, -S, and WRC-B, -S	3	2	0.301	100-338
FIRE SAFETY DEVICES PVT LTD. and Models FRC-B, -S, and WRC-B, -S	3	3	0.512	188-793
FIRE SAFETY DEVICES PVT LTD. and Models FRC-B, -S, and WRC-B, -S	3	6	0.944	1162
FIRE SAFETY DEVICES PVT LTD. and Models FRC-B, -S, and WRC-B, -S	3	8	1.417	1337

NOZZLES

Manufacturer and Model	Size, in.	Inlet Pressure, psig	Fuel
ANGUS FIRE LTD, Model: F225U	2-1/2	57	--

FOAM WATER SPRINKLERS

Manufacturer and Model	Fuel	Style	Minimum Pressure, psig
TYCO FIRE & BUILDING PRODUCTS, Model: B-1	Hydrocarbons	Pendent	30

Report Date: 2026-07-20
Revision Date: 2026-07-20

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."