

Model BT-5502-1200

File Number: EX29955

COMPANY

Blazetech Systems Ltd

100 Avebury Boulevard

Milton Keynes, MK9 1FH United Kingdom

MODEL INFO

BT-5502-1200

Limited Flexibility

PRODUCT INFORMATION

Hose Type	Rated Pressure, psig (kPa)	Max Ambient Temp, °F (°C)	Nom Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in. (mm)
Braided	200 (1378)	225 (107)	3.9 (1190)	7	3.0 (77)

GENERAL

Nom Inlet by Outlet Size, NPT	Inlet Fitting Connection	Outlet Fitting Connection	Max K-Factor of Sprinkler, gpm/vpsi (l/min/vbar)	Eq. Len. of Sch. 40 Steel Pipe (C = 120), ft (m)
1 by 1/2	--	--	--	29 (8.9)
1 by 3/4	--	--	--	31 (9.5)

INTENDED TO BE INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S BRACKETS AND INSTALLATION INSTRUCTIONS AS FOLLOWS

Brackets	Installation Instructions Date
MS(Center bracket) and EPT(End bracket)	2026.03.15
MS(Center bracket) and EPC(End bracket)	2026.03.15
ML(Center bracket) and EPT-L(End bracket)	2026.03.15
ML(Center bracket) and EPC-L(End bracket)	2026.03.15

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."