



SIN BL 5606

File Number: EX30031

COMPANY
Blazetech Systems Ltd
100 Avebury Boulevard
Milton Keynes, MK9 1FH United Kingdom

SIN INFO
BL 5606
Glass Bulb Type

ATTRIBUTES				
Response Type	Sprinkler Type	Nom K-Factor, gpm/vpsi (L/min/vbar)	System Working Pressure	Corrosion Resistant
QR	Standard Sidewall Spray Sprinklers	5.6 (80)	175 psig (1.2 Mpa)	Not Available

GENERAL	
Inlet Connection	
1/2 in. NPT	

STANDARD SIDEWALL SPRAY SPRINKLERS				
Type	Distance Below Ceiling, in. (cm)	Occupancy Hazard	Sprinkler Temp Rating, °F (°C)	Cover Temp Rating, °F (°C)
Rec. HSW	--	Light	135 (57), 155 (68), 175 (79), 200 (93)	Not Applicable
HSW	--	Light, Ordinary	135 (57), 155 (68), 175 (79), 200 (93)	Not Applicable

Report Date: 2026-08-24
Revision Date: 2026-08-24

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."