



SIN BL 5639

File Number: EX30031

COMPANY
Blazetech Systems Ltd
100 Avebury Boulevard
Milton Keynes, MK9 1FH United Kingdom

SIN INFO
BL 5639
Glass Bulb Type

ATTRIBUTES				
Response Type	Sprinkler Type	Nom K-Factor, gpm/vpsi (L/min/vbar)	System Working Pressure	Corrosion Resistant
SR	Conventional (Old Style) Sprinklers	5.6 (80)	175 psig (1.2 Mpa)	Not Available

GENERAL				
Inlet Connection				
1/2 in. NPT				

CONVENTIONAL (OLD STYLE) SPRINKLERS				
Sprinkler Temp Rating, °F (°C)				
135 (57), 155 (68), 175 (79), 200 (93), 286 (141), 360 (182)				

Report Date: 2026-08-24
Revision Date: 2026-08-24

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."